

RECTANGULAR DISPLACEMENT TERMINALS

TYPE: PFGR

RECTANGULAR UNIT PFGR

■ DESCRIPTION

Supply air for all types of premises. PFGR is made of sheet steel and powder coated in white RAL 9010. Internal air deflectors deliver even air distribution. PFGR can be obtained in other dimensions etc. Please contact Spread Air.

■ GENERAL DATA

Unit sizes: Ø100 - Ø500.
Airflow rates: 20-2000 l/s.
Design leaving air temperature: 6°C below room air temperature. If Δt is higher, the PFGR can be equipped with an induction chamber. It is then designated IPFGR. Pressuredrop with LP, SP approx. 70 Pa.

■ ACCESSORIES

Attenuator type LP. Damper (SP)
Duct cover (IK), to suit room height Rh. Plinth (GS), standard height 50 mm. Angle mounting strips for flushmounting.
Reinforced front type BUMPER.



RECTANGULAR FLUSH MOUNTED TERMINALS

TYPE: VIGR

RECTANGULAR UNIT FOR FLUSH MOUNTING VIGR

■ DESCRIPTION

Supply air for all types of premises. VIGR is made of sheet steel and powder coated in white RAL 9010. Internal air deflectors deliver even air distribution.

■ GENERAL DATA

Unit sizes: 5030, 5040, 5050, 5560, 5580, 5590.
Airflow rates: 20-100 l/s.
Design leaving air temperature: 6°C below room air temperature.
Pressuredrop: approx. 10-20 Pa.

■ ACCESSORIES

Connection sleeve made of galvanised sheet steel. The inside of the sleeve is covered with cleanable sound insulation, Renodemp.
Standard length 2 m. (Delivered in two pieces.)

